

Durashade

SPECIFICATION V1

INTRODUCTION

The Durashade collection of rigid PVC vertical blinds combines practicality and style. Durashade offers contemporary designs with the added benefits of durability and functionality. Suited to an office or medical environment, the collection is flame retardant (tested to BS5867) and easy to maintain and clean; with no requirement for stabilising chains or bottom weights, the Durashade collection resists the growth of bacteria and mould, making it ideal for moist conditions.

Comprised of 8 ranges in various colours and textures from linear and double-sided designs to metallic hues and high gloss, the collection meets the desires of interior trends for the ultimate in stylish functionality.



DURASHADE COLOURWAYS



RANGE	COLOUR
	Carbon
	Gesso
Kuta	Luna
	Selene
	Vapour
	Carbon
	Gesso
O cca	Luna
	Selene
	Vapour
	Carbon
	Gesso
Serino	Luna
	Selene
	Vapour
	Carbon
	Gesso
Turilli	Luna
	Selene
	Vapour
	Carbon
	Gesso
Zurich	Luna
	Selene
	Vapour
A	Cream
Amari	White
Carrera	Cream
	White
Perlato	White
	Cream

CRUZE VERTICAL

Cruze vertical headrail is standard on Durashade

	STANDARD	OPTIONAL
Slat Width	89mm	n/a
Headrail Colour	Gloss White	Matt White or Anthracite
Tilt Control	Right Hand Side	Left Hand Side
Draw Control	Right Hand Side	Left Hand Side
Open Cord	White	Anthracite
Operation	Direct Drive	Reduction Gear or Wand Control
Tilt Chain	White	Anthracite, Copper, Nickel or Gold
Louvre Bunch	Split	Left, Right or Centre
Bracket	Top Fix Spring	Shallow Frame (89mm, 127mm or 135mm)
Child Safety	Cruze Tie Down Clip	n/a
Min Control Length	Cruze Direct Drive – 195mm	n/a
	Cruze Reduction Gear – 460mm	n/a
	Cruze Vertical Wand Control – 150mm	n/a
Deduction from floor for	Cruze Direct Drive – 1500mm	n/a
control length (when install height provided)	Cruze Reduction Gear – 1500mm	n/a
	Cruze Vertical Wand Control – n/a	n/a
	Cruze Direct Drive – 1695mm	n/a
Min Installation Height	Cruze Reduction Gear – 1960mm	n/a
	Cruze Vertical Wand Control – n/a	n/a

TRAKONE SPECIFICATION

	STANDARD	OPTIONAL
Slat Width	89mm	n/a
Headrail Colour	White	n/a
Tilt Control	Right Hand Side	Left Hand Side
Draw Control	Right Hand Side	Left Hand Side
Open Cord	White	n/a
Operation	Direct Drive	Wand Control
Tilt Chain	Nickel	White
Louvre Bunch	Split*	Left or Right
Bracket	Trakone Top Fix Spring	Trakone Shallow Frame (89mm, 127mm)
Child Safety	Tie Down Clip	n/a
Min Control Length	Trakone Chain Opertaion - 460mm Trokone Wand Control - 150mm	n/a
Deduction from floor for control length (when install height provided)	Trakone Chain Operation – 1500mm	n/a
	Trakone Vertical Wand Control – n/a	n/a
Min Installation Height	Trakone Vertical Headrail – 1960mm	n/a
	Trakone Vertical Wand Control – n/a	n/a

^{*}Split bunch not available with wand control

EXCEL VERTICAL HEADRAIL

	STANDARD	OPTIONAL
Slat Width	89mm	n/a
Headrail Colour	White	Silver
Tilt Control	Right Hand Side	Left Hand Side
Draw Control	Right Hand Side	Left Hand Side
Open Cord	White	Grey
Operation	Direct Drive	Wand Control
Tilt Chain	Nickel	White
Louvre Bunch	Split	Left, Right or Centre
Bracket	Top Fix Spring	Face Fix or Shallow Frame (89mm, 127mm or 135mm)
Child Safety	Tie Down Clip	n/a
Min Control Length	Excel Vertical Headrail – 180mm Excel Vertical Wand Control – 150mm	n/a
Deduction from floor for control length (alter so provided not split over two lines)	Excel Vertical Headrail – 1500mm	n/a
	Excel Vertical Wand Control – n/a	n/a
Min Installation Height	Excel Vertical Headrail – 1690mm	n/a
	Excel Vertical Wand Control – n/a	n/a

RECOMMENDED BLIND SIZE

Durashade blinds are produced with an operating tolerance of +/- 3mm width and +/- 5mm drop

	MINIMUM	MAXIMUM
Width	250mm	5000mm
Drop	100mm	3500mm

WIDTH OF HEADRAIL

WIDTH OF HEADRAIL	NUMBER OF BRACKETS
250mm – 1000mm	2
1001mm – 1500mm	3
1501mm – 2000mm	4
2001mm – 2500mm	5
2501mm – 3000mm	6
3001mm – 3500mm	7
3501mm – 4000mm	8
4001mm – 4500mm	9
4501mm – 5000mm	10

BRACKET OPTIONS

Additional Information

Punch hole size – 6m (wide) x 4mm (height) Hole punch position – 6mm from top of slat


Finished cut slat is curved at top and bottom




Sloping headrails are available on request. Longest drop, shortest drop and slope width measurements are required when ordering, in recess size. Max. recommended angle of sloping blind is 35 degrees of the horizontal position.

Wand control is available at no additional cost. **Not available on slopping headrails.**


Top Fix Spring Bracket




Shallow Frame 89mm



Shallow Frame 135mm



Shallow Frame 127mm



MAINTENANCE

The product is low maintenance; however, we recommend that regular visual checks are completed to ensure that no components have been damages, which could result in operating difficulties and/or cause a safety risk. If any maintenance is required, we recommend that the work is carried out immediately by a reputable blind company.

